

Datasheet AT7-50

Powerful performance. Compact design. Smart price.

AT7-50 is the go-to tracking camera for immersive environments that require precision and reliability — at a lower cost. Suitable for use in e.g. Powerwalls, CAVEs, HMD arenas, and for a wide range of other applications.

You can also use it as a complement to existing AT7-80 systems:

The AT7-50 excels at improving tracking coverage - especially in occluded areas and corners.



Technical Data

General Camera Data	
Image sensor	2464 x 2064 Pixel
Adjustable frame rate	20 - 500 Hz
Minimum Latency	2.3 ms
Image processing	integrated
IR source	High power LEDs, 850 nm, adjustable in intensity (exempt group according to IEC62471-1)
Max. passive camera-to-marker range	17m ¹
Status indicator	Configurable RGB LED ring 2-digit alphanumeric display 2 status LEDs all dimmable until off
Data transfer, sync and power supply	Gigabit Ethernet PoE+ (IEEE 802.3at) max. 100 m cable (CAT5)
Mounting	ART D2 ceiling mount Tripod thread (x2); type 1/4-20 UNC
Operating conditions	
Cooling	Passive, fanless
Operating temperature	0 - 35°C
Relative humidity	5 - 85% (non-condensing)
Max. power consumption	16 W
Dimensions	
Size (W x H x D)	Approx. 83 x 84 x 78 mm
Weight	0.65 kg

		Camera configuration			
Lenses	Sensor Area (pixels)	Operation modes			
		@ 230 Hz	@ 270 Hz	@ 360 Hz	@ 500 Hz
3.5 mm	FoV (horiz. x vert.) [deg]	2464 x 2064	2464 x 1728	2464 x 1152	2464 x 752
4.5 mm		109 x 90	109 x 75	109 x 49	108 x 32
6.0 mm		83 x 70	83 x 58	83 x 39	83 x 25
		62 x 52	62 x 44	62 x 29	62 x 19
	Camera latency [ms]	4.7	4.1	3.0	2.3

Certifications
<ul style="list-style-type: none"> • CE • FCC Part 15 Subpart B, Class B • TÜV SÜD NRTL

¹ measured with 12.7mm passive markers, centric distance, sensor gain of 4 and 6 mm lens

Technical Drawing

all dimensions in [mm] unless otherwise specified

